Manual Codes (EPI/S-X): U11-C04D

Derwent Registry Numbers: 0245-U; 0270-U; 0306-U; 0323-U; 0325-U; 0335-U; 0366-U; 0367-U; 0377-U; 0804-U; 0862-U; 0879-U; 0904-U; 1066-U; 1713-U;

1740-U: 1881-U

21/9/2 DIALOG(R) File 351: DERWENT WPI (c)1997 Derwent Info Ltd. All rts. reserv.

010876091

WPI Accession No: 96-373042/199638

XRAM Accession No: C96-118423 XRPX Accession No: N96-313866 Method of making photoresist compsn. with reduced solvent waste comprising fractionation of polymeric binder resin(s) with supercritical

fluid, and admixture of resin(s) with photoresist cpd(s). Patent Assignee: OCG MICROELECTRONIC MATERIALS INC (OCGM-N)

Inventor: JEFFRIES A T; TOUKHY M A

Number of Countries: 004 Number of Patents: 002

Patent Family:

Patent No Kind Date Applicat No Kind Date Main IPC Week

EP 727711 A2 19960821 EP 96300988 A 19960213 G03F-007/004 199638 B JP 8248633 A 19960927 JP 9628793 A 19960216 G03F-007/032 199649

Priority Applications (No Kind Date): US 95390002 A 19950217

Patent Details:

Patent Kind Lan Pg Filing Notes Application Patent

EP 727711 A2 E 9

Designated States (Regional): DE FR NL

JP 8248633 A 9

Abstract (Basic): EP 727711 A

A method of making a photoresist compsn. comprises:

- (a) fractionating polymeric binder resin(s) with a supercritical
- (b) admixing or reacting the fractionated polymeric binder resin with photoresist cpd(s). (P).

Cpd. (P) comprises:

- (i) a photo [sic: photoactive] cpd.; and/or
- (ii) photo acid generator(s).

USE - Compsns. are esp. used in positive-working photoresist for

processing of Si wafer or GaAs wafer to form semiconductor devices.

ADVANTAGE - Prodn. of solvent waste is reduced or eliminated. Photo acid generators (PAG) increase dissolution rate of photoresist films to make positive-tone photoimage. Pref. supercritical fluid (SCF) is CO2 which is safe, non-toxic, inexpensive and readily commercially available.

Dwg.0/0

Title Terms: METHOD; PHOTORESIST; COMPOSITION; REDUCE; SOLVENT; WASTE; COMPRISE; FRACTIONATE; POLYMERISE; BIND; RESIN; SUPERCRITICAL; FLUID;

ADMIXED; RESIN; PHOTORESIST; COMPOUND

Derwent Class: A21; A89; G06; L03; P84; U11

International Patent Class (Main): G03F-007/004; G03F-007/032

International Patent Class (Additional): C08L-061/06; G03F-007/039;

H01L-021/027

File Segment: CPI; EPI; EngPI